SYSTEM KAN-therm

Install your future



Manifolds InoxFlovv

- Noble, top quality material
 stainless steel
- Twice as much flow compared to the brass products
- High resistance to chloride ions
- Modern design
- 100% European manufacture







Manifolds InoxFlow

Noble material

with high resistance to chloride ions in water (suitable particularly for drinking water systems)

Simple circuit identification

thanks to laser numbering on the beams and special descriptive labels to stick inside the cabinet

Easy Identification

laser marking to quarantee product authenticity

Rotatable beam

180° without the need of disassembling the manifold



Doubled hydraulic performance

compared to brass manifolds and possible connection of more heating circuits thanks to 1 1/4" beams made of 1.4301 stainless steel



Durable clamps

designed by professionals keeping up with the latest industrial trends. Vibration damping function to guarantee quiet system operation

Clear marking

of the connection method (supply/return)



Compatibility

with the existing KAN-therm manifold equipment (reducers, air vents, tees, etc.)



Convenient

outlets to individual circuits - 3/4" Eurocone

Complete offer

for all applications

Manifolds for central heating and drinking water (R)



Manifolds with 1/2" female outlets - RBB series



Manifolds with 3/4" nipples - RNN series



Manifolds with 3/4" nipples and cut off valves - RVV series

Cover*



* ordered separatly, available in anthracite or steel colour

Manifolds for underfloor heating (U)

witch control valves



Manifolds with control valves - UVN series



Manifolds with control and actuator valves

- UVS series



Manifolds with control and actuator valves and venting section

- UVST series

with flowmeters




Manifolds with Manifolds with flowmeters flowmeters and - UFN series actuator valves

- UFS series




Manifolds with flowmeters and actuator valves and venting section - **UFST** series

Manifolds for underfloor heating with integrated mixing unit (P)



Manifolds with control and actuator valves and a mixing unit with Wilo Para 25/6 pump - USVP series



Manifolds with flowmeters and actuator valves and a mixing unit with Wilo Para 25/6 pump - USFP series

MARKING OF MANIFOLD SERIES



T, A or P R or U B,N,S,V or F

> equipment of top or bottom beams Basic

Radiator Nipples Servomotor valves Underfloor heating manifolds for underfloor heating

Valves shut-off or balancing valves Flowmeters

additional

Top air-vent on top of the beam

Axis air-vent in the axis of the beam Pump mixing unit

KAN Group

e-mail: kan@kan-therm.com