

**CERT**

DVGW type examination certificate

DVGW-Baumusterprüfzertifikat

DW-8501AU2346Registration Number
Registriernummer

Field of Application <i>Anwendungsbereich</i>	products of water supply <i>Produkte der Wasserversorgung</i>
Owner of Certificate <i>Zertifikatinhaber</i>	REHAU AG + Co Ytterbium 4, D-91058 Erlangen
Distributor <i>Vertreiber</i>	REHAU AG + Co Ytterbium 4, D-91058 Erlangen
Product Category <i>Produktart</i>	installation systems and system joints: drinking water installation system (8501)
Product Description <i>Produktbezeichnung</i>	drinking water installation system consisting of pushing sleeve connector made of metal (brass, gunmetal and stainless steel) respectively made of plastic (PPSU) and multilayer pipes: PE-Xc/Al/PE-HD (RT) respectively PE-Xa/Al/PE-HD (RT)
Model <i>Modell</i>	System: RAUTITAN stabil
Test Reports <i>Prüfberichte</i>	supplement test: 201453/19-I from 20.04.2020 (SKZ) supplement test: 129715/18-I from 30.01.2019 (SKZ) supplement test: 11635/15 from 28.11.2017 (SKZ) supplement test: 116705/15 from 09.03.2015 (SKZ) supplement test: B441/14.3 from 11.02.2015 (IMA)
Test Basis <i>Prüfgrundlagen</i>	DVGW W 534-(P) (01.07.2015) DVGW CERT ZP 8500 (09.03.2017) UBA METALLE (21.11.2018) UBA KTW (07.03.2016) UBA Übergangsregelung KTW-BWGL (11.03.2019) DVGW W 270 (01.11.2007)
Date of Expiry / File No. <i>Ablaufdatum / Aktenzeichen</i>	31.08.2025 / 19-0344-WNV

11.05.2020 GI A-1/2

Date, Issued by, Sheet, Head of Certification Body
Datum, Bearbeiter, Blatt, Leiter der Zertifizierungsstelle

DVGW CERT GmbH is an accredited body by DAkkS according to DIN EN ISO/IEC 17065:2013 for certification of products for energy and water supply industry.

DVGW CERT GmbH ist von der DAkkS nach DIN EN ISO/IEC 17065:2013 akkreditierte Stelle für die Zertifizierung von Produkten der Energie- und Wasserversorgung.

Deutsche
Akkreditierungsstelle
D-ZE-16028-01-05DVGW CERT GmbH
ZertifizierungsstelleJosef-Wirmer-Str. 1-3
53123 BonnTel. +49 228 91 88 - 888
Fax +49 228 91 88 - 993www.dvgw-cert.com
info@dvgw-cert.com

Type Typ	Technical Data Technische Daten	Remarks Bemerkungen
RAUTITAN stabil; RAUTITAN stabil platinum	nominal diameter: 16 mm	unpressed leaky
RAUTITAN stabil; RAUTITAN stabil platinum	nominal diameter: 20 mm	unpressed leaky
RAUTITAN stabil; RAUTITAN stabil platinum	nominal diameter: 25 mm	unpressed leaky
RAUTITAN stabil; RAUTITAN stabil platinum	nominal diameter: 32 mm	unpressed leaky
RAUTITAN stabil; RAUTITAN stabil platinum	nominal diameter: 40 mm	unpressed leaky
RAUTITAN stabil RAUTITAN stabil	nominal diameter: 50 mm nominal diameter: 63 mm	

Hints of Utilization / Remarks

Verwendungshinweise / Bemerkungen

only to use with multilayer pipe:

PE-Xc/Al/PE-HD (RT)-pipe "Becker Plastics" (DW-8217AT2505): Ø 16 mm; Ø 50 mm; Ø 63 mm

RAUTITAN stabil / RAUTITAN stabil platinum (DW-8209BQ0171): Ø 16-40 mm

only to use with pushing sleeve connectors:

-basic body made of brass or gunmetal, pushing sleeve made of brass: Ø 16-40 mm
(pushing sleeve Ø 32-40 mm varnish coated)

-basic body made of stainless steel, pushing sleeve made of brass: Ø 16-40 mm
(pushing sleeve Ø 32-40 mm varnish coated)

-basic body made of brass or gunmetal, pushing sleeve made of plastic (PVDF): Ø 16-63 mm

-basic body made of stainless steel, pushing sleeve made of plastic (PVDF): Ø 16-40 mm

-basic body made of plastic (PPSU), pushing sleeve made of plastic (PVDF): Ø 16-40 mm